

FOOD WATER/15BL/EXTRA

H.T. - FOOD QUALITY - F.D.A. - W.P. 15 BAR - t. +120°C

IT IMPIEGO

Tubo in gomma long length idoneo per mandata di acqua calda in impieghi dove sia richiesta alimentarietà dei prodotti convogliati.

Normative di riferimento: DM 21/3/73 e 18/6/79 + F.D.A.

- **TEMPERATURA:** -35°C +120°C

STRUTTURA

- **Sottostrato:** liscio in gomma bianca EPDM alimentare resistente al calore.
- **Rinforzi:** inserzioni di filati sintetici ad alta resistenza.
- **Copertura:** in gomma blu EPDM resistente all'abrasione, al calore e all'invecchiamento.
- **Superficie:** liscia estrusa.
- **Marcatura:** ad inchiostro "H.T. - FOOD QUALITY F.D.A. - W.P. 15BAR +120°C".

EN APPLICATION

Long length rubber hose suitable for delivery of hot water where an food use hose is required.

Standards: DM 21/3/73 e 18/6/79 + F.D.A.

- **TEMPERATURE RANGE:** -35°C +120°C

CONSTRUCTION

- **Tube:** white, smooth, heat resistant food-quality EPDM rubber.
- **Reinforcement:** high strength synthetic textile yarn.
- **Cover:** blue, abrasion, heat and ageing resistant EPDM rubber.
- **Surface:** smooth extruded.
- **Branding:** ink marking "H.T. - FOOD QUALITY F.D.A. - W.P. 15BAR +120 °C".

DIAMETRO INTERNO INSIDE DIAMETER		DIAMETRO ESTERNO OUTSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESS. SCOPPIO BURST PRESSURE		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	mt	ft
13	1/2"	22	7/8"	0.31	0.20	15	225	45	675	40	131
16	5/8"	25	1"	0.35	0.23	15	225	45	675	40	131
19	3/4"	29	1.5/32"	0.48	0.32	15	225	45	675	40	131
25	1"	36	1.13/32"	0.80	0.53	15	225	45	675	40	131

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.