

JABSCO PUPPY SERIES

Model No.	Body Materials	Impeller	Seal	Voltage	Amp Draw	Fuse Size	Motor Type	Port Type	Weight
18620-0003	Bronze	Nitrile	Lip Type	12 (Vdc)	7 (amp)	10 (amp)	Reversible permanent magnet type with Integral reversing switch and fuse	3/4" garden hose external	5.5 lb. (2.5 kg)
18660-0121	Bronze	Neoprene	Lip type	12 (Vdc)	8 (amp)	15 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft	1/2" internal pipe threads and 1" external hose barb adapter for 3/4" external garden hose thread included	4.5 lb. (2 kg)
18660-0123	Bronze	Nitrile	Lip type	12 (Vdc)	8 (amp)	15 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft	1/2" internal pipe threads and 1" external hose barb adapter for 3/4" external garden hose thread included	4.5 lb. (2 kg)
18650-0121	Bronze	Neoprene	Lip type	12 (Vdc)	7 (amp)	15 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft	3/8" internal pipe threads and 1" external hose barb adaptor for 3/4" external garden hose thread included	4.5 lb. (2 kg)
18670-0123	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	11.5 (amp)	20 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft, ball type shaft bearing, adequate torque to reverse the pump	1/2" internal pipe threads and 1" external hose barb adapter for 3/4" external garden hose thread included	6 lb. (2.7 kg)
18670-0923	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	11.5 (amp)	20 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft, ball type shaft bearing, adequate torque to reverse the pump	1/2" internal pipe threads and 1" external hose barb adapter for 3/4" external garden hose thread included	6 lb. (2.7 kg)
18670-0943	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	5 (amp)	10 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft, ball type shaft bearing, adequate torque to reverse the pump	1/2" internal pipe threads and 1" external hose barb adapter for 3/4" external garden hose thread included	6 lb. (2.7 kg)
23610-3003	Bronze	Nitrile	Lip type	12 or 24 (Vdc)	21 (amp)	25 (amp)	Permanent magnet, continuous rated	1/2" BSP or 1" hose barb	7.5 lb. (3.4 kg)
23610-3103	Bronze	Nitrile	Lip type	12 or 24 (Vdc)	11 (amp)	15 (amp)	Permanent magnet, continuous rated	1/2" BSP or 1" hose barb	7.5 lb. (3.4 kg)
23620-4003	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	5 (amp)	7.5 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft, ball type bearings	1" ID hose	5.0 lb. (2.3 kg)
23620-4103	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	2.5 (amp)	5 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft, ball type bearings	3/8" hose	5.0 lb. (2.3 kg)
23670-4003	Brass	Nitrile	Lip Type	12 (Vdc)	13 (amp)	15 (amp)	Permanent magnet type, fully enclosed, continuous rated, stainless steel shaft, ball type bearings	3/8" BSP or 1" ID hose	6.6 lb. (3 kg)

JABSCO PUPPY SERIES

Model No.	Body Materials	Impeller	Seal	Voltage	Amp Draw	Fuse Size	Motor Type	Port Type	Weight
23670-4103	Brass	Nitrile	Lip Type	24 (Vdc)	7 (amp)	10 (amp)	Permanent magnet type, fully enclosed, continuous rated, stainless steel shaft, ball type bearings	3/8" BSP or 1" ID hose	6.6 lb. (3 kg)
23680-4003	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	13 (amp)	15 (amp)	Permanent magnet	1/2" BSP or 1" hose barb	6.6 lb. (3 kg)
23680-4103	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	6 (amp)	10 (amp)	Permanent magnet	1/2" BSP or 1" hose barb	6.6 lb. (3 kg)
23920-2423	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	13 (amp)	15 (amp)	Permanent magnet, continuous rated	3/4" BSP	7 lb. (3.3 kg)
23920-2523	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	7 (amp)	10 (amp)	Permanent magnet, continuous rated	3/4" BSP	7 lb. (3.3 kg)
23920-9423	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	13 (amp)	15 (amp)	Permanent magnet, continuous rated	NPT (19mm)	7 lb. (3.3 kg)
23920-9523	Bronze	Nitrile	Lip Type	12 or 24 (Vdc)	7 (amp)	10 (amp)	Permanent magnet, continuous rated	NPT (19mm)	7 lb. (3.3 kg)
8860-0001	Bronze	Neoprene	Lip Type	12 (Vdc)	4 (amp)	10 (amp)	Permanent magnet type, fully enclosed, stainless steel shaft	3/8" pip thread internal plus an adaptor for 3/4" garden hose thread	4.5 lb. (2 kg)